

Seattle Fire Marshal's Office 220 3<sup>rd</sup> Avenue South, 2<sup>nd</sup> Floor Seattle, WA 98104 (206) 386-1443 sfd\_fmo\_engineering@seattle.gov

## RADIO COVERAGE SIGNAL STRENGTH ASSESSMENT FORM

SFC 510.1 (Exception #1)

## Assessment of Signal Strength without BDA/DAS for Buildings That Require Minimum Emergency Responder Radio Coverage

	gog	, openial of the age				
□Coverage me building	eets code requirements throughout the	☐Coverage does not meet code requirements in part or all of the building				
	ERN Towers (Optional starting 1/1/2023 ERS Towers (Not allowed for projects of	· · · · · · · · · · · · · · · · · · ·				
emergency resp (BDAs) or Distril construction sha anticipated tena in the exterior but	conder radios and therefore do not requibuted Antenna Systems (DAS). If used in the completed prior to radio signal test in the improvements. In-building signal streatile in the improvement and interior tenant improvement and interior tenant improvement.	a building) have adequate public safety radio signal strength for re radio amplification systems such as Bi-Directional Antennas in conjunction with a new construction project, shell and core sing, and assumptions shall be provided for signal limitations from ngth can change over time for many reasons including changes overments. If signal strength becomes insufficient in the future, ults documented on this form at this time.				
SECTION 4	DIJU DINC INCODMATION					
SECTION 1	BUILDING INFORMATION					
Building Name:						
Building Address:						
SECTION 2 TESTING COMPANY, TECHNICIAN AND EQUIPMENT						
Section 2.1 Testing Company Information						
Company Name	):	Contact Name:				
Mailing Address:		Phone:				
		Email:				
Section 2.2 Technician Information						
Technician Name:		Phone:				
Technician FCC	Certification/GROL#:					
Technician performing testing has received manufacturer training or other equivalent: □Yes □No						
Specify manufac	cturer training received and year:					
Section 2.3 Testing Equipment Used for Assessment						
Spectrum analyzer make/model**:						
Spectrum analyzer calibration date:						
Calibration performed by firm (qualified firm name):*  ** Use of a calibrated spectrum analyzer, with a current calibration, is required for this testing.						

SECTI	ON 3	RADIO COVERAGE ASSESSMENT RESULTS						
Date of Assessment:								
Pass	covera	tire building in its current configuration provides adequate PSERN or KCE ge in 90% of all areas of each floor of the building and 99% of the area of where coverage requirements are defined in 2018 Seattle Fire Code 510.	critical	□Yes	□No			
Partial	The fol	lowing portions of the building in the current configuration provide adequa RS signal coverage and should not need any additional DAS infrastructur stors such as directional, floor, wing):						
	covera	lowing portions of the building do not provide adequate PSERN or KCERS ge and will need additional DAS infrastructure to improve signal strength a le requirements (include descriptors such as directional, floor, wing):	•	□Yes	□No			
Fail		ilding area provides inadequate PSERN or KCERS signal coverage and v nal DAS infrastructure to improve signal strength and meet fire code requi		□Yes	□No			
SECTION 4 REQUIRED DOCUMENTATION								
<ul> <li>A copy of the following documents is attached to this report for the fire code official.</li> <li>4.1 Grid diagram for each floor, showing test signal strengths in each floor, and indicating location of each critical area.</li> <li>4.2 Copy of General Radiotelephone Operator's License for technician listed in section 2.2 above.</li> <li>4.3 The form and attachments are stored in the fire command center or building engineer's office</li> </ul>		g location	□Yes	□No				
		□Yes	□No					
AND submitted by email to the Seattle Fire Department.			□Yes	□No				
By accepting this statement I, the FCC-licensed technician shown on this form, certify that I have properly assessed radio signal strength following NFPA and SFC standards and have accurately provided results in section 3 above, indicating whether the building or portions of the building have signal strength meeting the requirements in SFC 510.4.1.			□Yes	□No				
SIGNATURE								
Signatu	ire of Te	echnician	Date					

## **INSTRUCTIONS FOR SUBMITTING THIS FORM TO SFD**

- 1. A paper copy of this form and the required documentation in section 4 shall be stored at the building and made available to representatives from the Fire Marshal's Office at the time of inspection.
- 2. Email form to SFD\_FMO\_engineering@seattle.gov at least 48 hours in advance of your SFD building final inspection to facilitate inspection scheduling and passing result. We recommend emailing forms to SFD as soon as they are available.